37.8 C.Y.


33.0 C.Y. 17.4 C.Y.

1.7 C.Y. 0.6 C.Y.

52.7 C.Y.

1,153 LBS.

90.5 C.Y.



HYDRAULIC DATA

DESIGN DISCHARGE = 280 C.F.S. FREQUENCY OF DESIGN FLOOD = 10 YEARS

DESIGN HIGH WATER ELEVATION = 2.8

DRAINAGE AREA = 2.1 SQ. MI.

BASE DISCHARGE (Q100) = 600 C.F.S. BASE HIGH WATER ELEVATION = 4.87

OVERTOPPING FLOOD DATA

OVERTOPPING DISCHARGE

= 1100 C.F.S.

FREQUENCY OF OVERTOPPING FLOOD = 500 YRS.+ OVERTOPPING FLOOD ELEVATION = 7.8

OVERTOPPING -DRV3- @ STA.19+91

GRADE DATA

GRADE PT. ELEV. @ STA. 20+75.75-DRV3- = 7.98 BED ELEV. @ STA. 20+75.75 -DRV3-= -2.40

ROADWAY FILL SLOPES = 3:1

ASSUMED LIVE LOAD = HL-93 OR ALTERNATE LOADING.

DESIGN FILL----- 2.41 FT. FOR OTHER DESIGN DATA AND NOTES, SEE STANDARD

NOTE SHEET. 3"Ø WEEP HOLES INDICATED TO BE IN ACCORDANCE

NOTES

WITH THE SPECIFICATIONS.

CONCRETE IN STAGE I & STAGE II TO BE POURED IN THE FOLLOWING ORDER:

- 1. STAGE I WING FOOTINGS AND FLOOR SLAB INCLUDING 4"OF ALL VERTICAL WALLS AS INDICATED IN THE CONSTRUCTION SEQUENCE.
- 2. THE REMAINING PORTIONS OF THE STAGE I WALLS AND WINGS FULL HEIGHT.
- 3. STAGE II WING FOOTINGS AND FLOOR SLAB INCLUDING 4" OF VERTICAL WALL AS INDICATED IN THE CONSTRUCTION SEQUENCE.
- 4. THE REMAINING PORTION OF THE STAGE II WALLS AND WINGS FULL HEIGHT. FOLLOWED BY ROOF SLAB, HEADWALLS.

THE RESIDENT ENGINEER SHALL CHECK THE LENGTH OF CULVERT BEFORE STAKING IT OUT TO MAKE CERTAIN THAT IT WILL PROPERLY TAKE CARE OF THE FILL.

DIMENSIONS FOR THE WING LAYOUT AS WELL AS ADDITIONAL REINFORCING STEEL EMBEDDED IN BARREL ARE SHOWN IN THE WING SHEET.

AT THE CONTRACTOR'S OPTION, HE MAY SPLICE THE VERTICAL REINFORCING STEEL IN THE INTERIOR FACE OF EXTERIOR WALL AND BOTH FACES OF INTERIOR WALLS ABOVE THE LOWER WALL CONSTRUCTION JOINT. THE SPLICE LENGTH SHALL BE AS PROVIDED IN THE SPLICE LENGTH CHART SHOWN ON THE PLANS. EXTRA WEIGHT OF STEEL DUE TO THE SPLICES SHALL BE PAID FOR BY THE CONTRACTOR.

FOR CULVERT DIVERSION DETAILS AND PAY ITEM, SEE EROSION CONTROL PLANS.

A 3 FOOT STRIP OF FILTER FABRIC SHALL BE ATTACHED TO THE FILL FACE OF THE WING COVERING THE ENTIRE LENGTH OF THE EXPANSION JOINT.

NO PRECAST REINFORCED BOX CULVERT OPTION WILL BE ALLOWED.

SILLS ARE TO BE PLACED ONE FOOT INSIDE EACH END OF THE CULVERT. THE CULVERT SHOULD BE BACKFILLED WITH NATIVE BED MATERIAL BED MATERIALS SUBJECT TO APPROVAL OF THE ENGINEER.

FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.

FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.

FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

FOR CONSTRUCTION SEQUENCE, SEE SHEET 7 OF 8.

STAGE I STRUCTURE QUANTITIES

CLASS A CONCRETE

19.0 C.Y. 17.6 C.Y. 1 BARREL 2 WINGS & CURTAIN WALLS 2 SILLS 1.2 C.Y.

REINFORCING STEEL

STAGE I CONCRETE

2,594 LBS. 1,153 LBS. 1 BARREL 2 WINGS

STAGE I REINFORCING STEEL 3.747 LBS.

FOUNDATION CONDITIONING MAT'L. 29.0 TONS CULVERT EXCAVATION LUMP SUM

STAGE II STRUCTURE QUANTITIES

CLASS A CONCRETE

1 BARREL & ROOF 2 WINGS & CURTAIN WALLS 2 HEADWALLS 2 SILLS

STAGE II CONCRETE REINFORCING STEEL

> 1 BARREL, ROOF, 3,757 LBS. 2 HEADWALLS & 2 SILLS

2 WINGS

STAGE II REINFORCING STEEL 4,910 LBS.

FOUNDATION CONDITIONING MAT'L. 19.0 TONS

LUMP SUM CULVERT EXCAVATION

TOTAL STRUCTURE QUANTITIES CLASS A CONCRETE

37.8 C.Y. STAGE I 52.7 C.Y. STAGE II __

REINFORCING STEEL

TOTAL

3,747 LBS. STAGE I

4,910 LBS. STAGE II _____ 8,657 LBS.

FOUNDATION CONDITIONING MATERIAL

29 TONS

19 TONS STAGE II _____ 48 TONS

CULVERT EXCAVATION LUMP SUM

> PROJECT NO. R-2514D JONES & CRAVEN COUNTY

STATION: 20+75.75 -DRV3-

SHEET 1 OF 8

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

DOUBLE 8 FT. X 8 FT. CONCRETE BOX CULVERT

92° SKEW

SHEET NO. **REVISIONS** C19-001 DATE: DATE:

STD. NO. CB12A

Tim Coggins

PROFILE ALONG & CULVERT

5′-7"

3′-3"

7′-9"

27'-1"

10'-8"

3′-5"

4'-0"

35'-0"

5′-5"

—-DRV3-

ASSEMBLED BY : M.D. PISO CHECKED BY : N. RUFFIN _ DATE : 01-09-15 | SPECIAL DRAWN BY : R.W. WRIGHT ____ DATE : <u>JULY.1990</u> ____ DATE : <u>JULY.1990</u> STANDARD CHECKED BY : D.A. GLADDEN

15'-0"